

PRODUCT SPECIFICATIONS SHEET

CATEGORY | STRIPLIGHT LUMINAIRES



KEY FEATURES


- **Power levels:** 5W/m / 15W/m / 20W/m
- **Luminaire efficacy:** Up to 110lm/W.
- **Heatsink:** Aluminium.
- **Mounting:** Surface.
- **Luminaire colour options:** White / Black / Custom colour on request.
- **LED lifetime (L80B10):** >75 000 hrs.
- **Dimming options:** DALI, Bluetooth, Touch DIM, 1-10, Triac, PWM.
- Luminaire supplied with external driver.

PHOTOMETRICS

LUMINAIRE DATA	NAME	VOLTS (V)	DRAW POWER (W/m)	LENGTH (mm) (INCREMENTS OF 86mm)	LED COLOUR (CCT)	COLOUR RENDERING INDEX (CRI)
	AKANDA	24	5	94mm - 2076mm	3000K, 3500K, 4000K, 5700K	92
	AKANDA	24	15	94mm - 2076mm	3000K, 3500K, 4000K, 5700K	92
	AKANDA	24	20	94mm - 2076mm	3000K, 3500K, 4000K, 5700K	92

LUMINAIRE DATA	NAME	DRAW POWER (W/m)	WIDTH (mm)	HEIGHT (mm)	NOMINAL FLUX (LM/m)	LUMINAIRE EFFICACY (LM/W)	MAX CONNECTED LGTH (m)
	AKANDA	5	20	18	450 - 550	90 - 110	6
	AKANDA	15	20	18	1350 - 1650	90 - 110	6
	AKANDA	20	20	18	1800 - 2200	90 - 110	4

PHOTOMETRICS



AKANDA

FIXTURE FEATURES AND WARRANTY



IP20



5Year
WARRANTY



GENERAL SPECIFICATIONS

GENERAL SPECIFICATIONS	DESCRIPTION	SPECIFICATION
	LED chip type	Samsung / Vossloh Schwable
	LED operating voltage	24V
	LED working life (L80B10)	>75 000hrs @ Ta = 25 deg C
	Driver type	External
	Driver dimming	Non - dim/ DALI / Bluetooth / Touch DIM / 1-10 / Triac / PWM
	IP rating	IP20
	SABS company certification	10089/15954
	Operating temperature range	0°C to +40°C
	Housing material	Aluminium/ PMMA

PRODUCT IMAGES



Perspective view