

PRODUCT SPECIFICATIONS SHEET

CATEGORY | FOOD DISPLAY LUMINAIRES



KEY FEATURES

- **Power level up to 20W/m.**
- **Luminaire efficacy:** Up to 95lm/W.
- **Heatsink:** Aluminium.
- **Mounting:** Surface mounted.
- **Luminaire colour options:** Anodised Aluminium
- **LED lifetime (L80B10):** >75 000 hrs.

PHOTOMETRICS

LUMINAIRE DATA	NAME	DRAW POWER (W)	LED COLOUR (CCT)	COLOUR RENDERING INDEX (CRI)	LUMINOUS FLUX (LM)	LUMINAIRE EFFICACY (LMW)	BEAM ANGLE
	FOGO - 250mm	2.5 / 3.75 / 5	3000K, 3500K, 4000K ,5700K, M EAT	90	237 - 475	95	120°
	FOGO - 530mm	5.3 / 7.9 / 10.6	3000K, 3500K, 4000K ,5700K, M EAT	90	503 - 1007	95	120°
	FOGO - 550mm	5.5 / 8.2 / 11	3000K, 3500K, 4000K ,5700K, M EAT	90	522 - 1045	95	120°
	FOGO - 660mm	6.6 / 9.9 / 13.2	3000K, 3500K, 4000K ,5700K, M EAT	90	627 - 1254	95	120°
	FOGO - 708mm	7 / 10.6 / 14.1	3000K, 3500K, 4000K ,5700K, M EAT	90	672 - 1345	95	120°
	FOGO - 746mm	7.4 / 11.1 / 14.9	3000K, 3500K, 4000K ,5700K, M EAT	90	708 - 1417	95	120°
	FOGO - 830mm	8.3 / 12.4 / 16.6	3000K, 3500K, 4000K ,5700K, M EAT	90	788 - 1577	95	120°
	FOGO - 876mm	8.7 / 13.1 / 17.5	3000K, 3500K, 4000K ,5700K, M EAT	90	832 - 1664	95	120°
	FOGO - 1014mm	10.1 / 15.2 / 20.2	3000K, 3500K, 4000K ,5700K, M EAT	90	963 - 1926	95	120°
	FOGO - 1100mm	11 / 16.5 / 22	3000K, 3500K, 4000K ,5700K, M EAT	90	1045 - 2090	95	120°
	FOGO - 1160mm	11.6 / 17.4 / 23.2	3000K, 3500K, 4000K ,5700K, M EAT	90	1102 - 2204	95	120°
	FOGO - 1176mm	11.7 / 17.6 / 23.5	3000K, 3500K, 4000K ,5700K, M EAT	90	1117 - 2234	95	120°
	FOGO - 1262mm	12.6 / 18.9 / 25.2	3000K, 3500K, 4000K ,5700K, M EAT	90	1198 - 2397	95	120°
	FOGO - 1476mm	14.7 / 22.1 / 29.5	3000K, 3500K, 4000K ,5700K, M EAT	90	1402 - 2804	95	120°
	FOGO - 1664mm	16.6 / 24.9 / 33.2	3000K, 3500K, 4000K ,5700K, M EAT	90	1580 - 3161	95	120°
	FOGO - 1750mm	17.5 / 26.2 / 35	3000K, 3500K, 4000K ,5700K, M EAT	90	1662 - 3325	95	120°
	FOGO - 1800mm	18 / 27 / 36	3000K, 3500K, 4000K ,5700K, M EAT	90	1710 - 3420	95	120°



IP20



5Year
WARRANTY

GENERAL SPECIFICATIONS

DESCRIPTION	SPECIFICATION
LED operating voltage	24V
LED working life (L80B10)	>75 000hrs @ Ta = 25 deg C
IP rating	IP20
SABS company certification	10089/15954
Operating temperature range	0°C to +30°C
Housing material	Aluminium / Polycarbonate
Product warranty	5 Years
Product weight excluding packaging	+/- 0.23kg/m
Product weight including packaging	+/- 0.30kg/m



Front view



Side view



Top view



Perspective view

ACCESSORIES



Accent mounting clip V11, opaque plastic with accent mounting o-ring, Clear PVC and pan head self taper



Luminis V2 surface bracket, metal with galvanized self drilling truss head



Terry / tool clip, 16mm stainless with pan head self taper



DC plug - black / white - 3.5m lead - 90°